# Semi-rotary drive
# DSM-T-40-270-FW-A-B

Part number: 1145132





## Data sheet

| Feature | Value |
|---|---|
| Size | 40 |
| Swivel angle | 0 deg...270 deg |
| Permissible stop radius | 40 mm |
| Mounting position | Any |
| Mode of operation | Double-acting |
| Design | Vane |
| Position detection | None |
| Operating pressure | 0.2 MPa...1 MPa<br>2 bar...10 bar |
| Max. swivel frequency at 0.6 MPa (6 bar, 87 psi) | 2 Hz |
| Operating medium | Compressed air to ISO 8573-1:2010 [7:-:-] |
| Note on operating and pilot medium | Lubricated operation possible (in which case lubricated operation will always be required) |
| Corrosion resistance class CRC | 0 - No corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B2-L |
| Ambient temperature | -10 °C...60 °C |
| Max. stop force | 650 N |
| Max. axial force | 120 N |
| Max. radial force | 350 N |
| Theoretical torque at 0.6 MPa (6 bar, 87 psi) | 40 Nm |
| Product weight | 3705 g |
| Type of mounting | With female thread |
| Pneumatic connection | G1/8 |
| Note on materials | RoHS compliant |
| Material drive shaft | Steel<br>nickel-plated |
| Material seals | TPE-U(PU) |
| Material housing | Anodised aluminium |