# Round cylinder
# DSNU-S-20-25-P-A-MX

Part number: 5224636





## Data sheet

| Feature | Value |
|---|---|
| Stroke | 25 mm |
| Piston diameter | 20 mm |
| Piston rod thread | M8 |
| Cushioning | Elastic cushioning rings/plates at both ends |
| Mounting position | Any |
| Design | Piston<br>Piston rod<br>Cylinder barrel |
| Position detection | Via proximity switch |
| Operating pressure | 0.08 MPa...1 MPa<br>0.8 bar...10 bar |
| Mode of operation | Double-acting |
| Operating medium | Compressed air to ISO 8573-1:2010 [7:4:4] |
| Note on operating and pilot medium | Lubricated operation possible (in which case lubricated operation will always be required) |
| Corrosion resistance class CRC | 2 - Moderate corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B2-L |
| Cleanroom suitability, measured according to ISO 14644-14 | Class 5 according to ISO 14644-1 |
| Ambient temperature | -20 °C...80 °C |
| Impact energy in end positions | 0.2 J |
| Theoretical force at 0.6 MPa (6 bar, 87 psi), return stroke | 158.3 N |
| Theoretical force at 0.6 MPa (6 bar, 87 psi), advance stroke | 188.5 N |
| Moving mass for 0 mm stroke | 37.3 g |
| Additional moving mass per 10 mm stroke | 4 g |
| Basic weight for 0 mm stroke | 126 g |
| Additional weight per 10 mm stroke | 7.2 g |
| Type of mounting | With accessories |
| Pneumatic connection | G1/8 |
| Note on materials | RoHS compliant |
| Material cover | Anodised wrought aluminium alloy |
| Material seals | TPE-U(PU) |
| Material piston rod | High-alloy stainless steel |

| Feature | Value |
| --- | --- |
| Material cylinder barrel | High-alloy stainless steel |