# Round cylinder
# DSNU-63-100-PPS-A

Part number: 559329





## Data sheet

| Feature | Value |
|---|---|
| Stroke | 100 mm |
| Piston diameter | 63 mm |
| Piston rod thread | M16x1.5 |
| Cushioning | Self-adjusting pneumatic end-position cushioning |
| Mounting position | Any |
| Design | Piston<br>Piston rod<br>Cylinder barrel |
| Position detection | Via proximity switch |
| Operating pressure | 0.1 MPa...1 MPa<br>1 bar...10 bar |
| Mode of operation | Double-acting |
| Operating medium | Compressed air to ISO 8573-1:2010 [7:4:4] |
| Note on operating and pilot medium | Lubricated operation possible (in which case lubricated operation will always be required) |
| Corrosion resistance class CRC | 2 - Moderate corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Ambient temperature | -20 °C...80 °C |
| Impact energy in end positions | 1.3 J |
| Cushioning length | 21 mm |
| Theoretical force at 0.6 MPa (6 bar, 87 psi), return stroke | 1681.9 N |
| Theoretical force at 0.6 MPa (6 bar, 87 psi), advance stroke | 1870.3 N |
| Moving mass | 709 g |
| Product weight | 1885 g |
| Type of mounting | With accessories |
| Pneumatic connection | G3/8 |
| Note on materials | RoHS compliant |
| Material cover | Wrought aluminium alloy |
| Material seals | NBR<br>TPE-U(PU) |
| Material piston rod | High-alloy steel |
| Material cylinder barrel | High-alloy stainless steel |