# ISO cylinder
# ESNU-10- -

Part number: 193997



## Data sheet

| Feature | Value |
|---|---|
| Stroke | 1 mm...50 mm |
| Piston diameter | 10 mm |
| Cushioning | Elastic cushioning rings/plates at both ends |
| Mounting position | Any |
| Conforms to standard | CETOP RP 52 P<br>ISO 6432 |
| Design | Piston<br>Piston rod<br>Cylinder barrel |
| Position detection | Via proximity switch |
| Variants | Extended male piston rod thread<br>Piston rod with male thread shortened at one end<br>Extended piston rod<br>Axial supply port<br>Piston rod at one end |
| Operating pressure | 0.15 MPa...1 MPa<br>1.5 bar...10 bar |
| Mode of operation | Pushing<br>Single-acting |
| Operating medium | Compressed air to ISO 8573-1:2010 [7:4:4] |
| Note on operating and pilot medium | Lubricated operation possible (in which case lubricated operation will always be required) |
| Corrosion resistance class CRC | 2 - Moderate corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Ambient temperature | -20 °C...120 °C |
| Impact energy in end positions | 0.05 J |
| Theoretical force at 0.6 MPa (6 bar, 87 psi), advance stroke | 36 N...37 N |
| Moving mass for 0 mm stroke | 8.5 g |
| Additional moving mass per 10 mm stroke | 1 g |
| Basic weight for 0 mm stroke | 37.3 g |
| Additional weight per 10 mm stroke | 2.7 g |
| Type of mounting | With accessories |
| Pneumatic connection | M5 |
| Note on materials | RoHS compliant |

| Feature | Value |
|---|---|
| Material cover | Wrought aluminium alloy |
| Material piston rod | High-alloy stainless steel |
| Material cylinder barrel | High-alloy stainless steel |